Appl. No. 09/737,226 Amdt. Dated February 9, 2004 Reply to Office Action of December 1, 2003

AMENDMENTS TO THE CLAIMS

- (Currently amended) An intra chip or intra mutli-chip module on a shared substrate multi-wavelength optical communication system comprising:
 - a number of emitters each of which emits radiation at a different wavelength;
 - a plurality of detectors each of which senses radiation at a different wavelength corresponding to the radiation from one of said emitters; and
 - a shared waveguide on the same substrate including a scattering medium configured with dispersive particles for transmitting emitted radiation to said detectors.
- 2. (Original) The multi-wavelength optical communication system of claim 1 in which said emitter includes a vertical cavity surface emitting laser.
- 3. (Original) The multi-wavelength optical communication system of claim 1 in which said emitter includes a scattering grating for redirecting the emitted radiation laterally through said shared waveguide.
- 4. (Original) The multi-wavelength optical communication system of claim 1 in which a said detector includes a filter for selectively passing one of said wavelengths from said emitters.
- 5. (Original) The multi-wavelength optical communication system of claim 4 in which said filter includes a Bragg grating.
- 6. (Original) The multi-wavelength optical communication system of claim 1 in which said shared waveguide scatters the lateral leakage radiation from said emitters.
- 7. (Original) The multi-wavelength optical communication system of claim 1 in which said emitter includes an LED.
- 8. (Original) The multi-wavelength optical communication system of claim 1 in which said emitter includes an edge emitting laser.

FEB-9-04

1:35PM;

Appl. No. 09/737,226 Amdt. Dated February 9, 2004 Reply to Office Action of December 1, 2003



SENT BY: MAINE & ASMUS;

- 9. (Original) The multi-wavelength optical communication system of claim 1 in which said emitter includes a reflector for redirecting the emitted radiation laterally through said shared waveguide.
- 10. (Original) The multi-wavelength optical communication system of claim 1 in which said emitters and detectors are disposed in a generally planar array.
- 11. (Original) The multi-wavelength optical communication system of claim 10 in which said shared waveguide is generally planar.
- 12. (Original) The multi-wavelength optical communication system of claim 1 in which said emitters and detectors are disposed on a chip.
- 13. (Original) The multi-wavelength optical communication system of claim 12 in which said chip is gallium arsenide.
- 14. (Original) The multi-wavelength optical communication system of claim 1 in which said chip is flip-chip bonded to a silicon chip.
- 15. (Original) The multi-wavelength optical communication system of claim 1 in which said shared waveguide is disposed on an integrated circuit chip to provide intrachip communications.
- 16. (Original) The multi-wavelength optical communication system of claim 1 in which said shared waveguide is disposed part on one integrated circuit chip and part on another integrated circuit chip to provide interchip communication.
- 17. (Original) The multi-wavelength optical communication system of claim 1 in which shared waveguide includes a reflective medium for containing the scattering radiation.
- 18. (Original) The multi-wavelength optical communication system of claim 17 in which a reflective medium is a lower index of refraction from the waveguide.



Appl. No. 09/737,226 Amdt. Dated February 9, 2004 Reply to Office Action of December 1, 2003

- 19. (Original) The multi-wavelength optical communication system of claim 1 in which said shared waveguide is disposed part on a plurality of chips mounted on a common substrate to provide interchip communication.
- (Original) The multi-wavelength optical communication system of claim 1 further 20. including an opaque barrier for absorbing the radiation.
 - (New) A multi-wavelength optical communication system comprising: 21. a number of emitters each of which emits radiation at a different wavelength; a plurality of detectors each of which senses radiation at a different wavelength corresponding to the radiation from one of the emitters; and a shared waveguide for transmitting radiation from the emitters to the detectors, the waveguide including a scattering medium configured with dispersive particles, and a reflective medium for containing scattering radiation.
 - 22. (New) A multi-wavelength optical communication system comprising: a number of emitters each of which emits radiation at a different wavelength; a plurality of detectors each of which senses radiation at a different wavelength corresponding to the radiation from one of the emitters; and a shared waveguide for transmitting radiation from the emitters to the detectors, the waveguide including a scattering medium configured with dispersive particles, wherein the shared waveguide is disposed part on one substrate and part on another substrate, thereby allowing communication between circuitry on the substrates.

SENT BY: MAINE & ASMUS;